

Type:

Model:

LED 2 × 2 Dimmable Panels
SPECIFICATIONS

AGENCY LISTINGS: UL approved (E481870).

WARRANTY: Five years.

Model	487601	487602	487603
Description	LED-2x2-DP-40W-3000K-WH	LED-2x2-DP-40W-4000K-WH	LED-2x2-DP-40W-5000K-WH
Voltage	120-277 V	120-277 V	120-277 V
Size	24 × 24 in	24 × 24 in	24 × 24 in
Wattage	40.23 W	40.31 W	40.39 W
Color Temperature	3000 K	4000 K	5000 K
Luminous Flux	3906.7 lm	4016.9 lm	4127 lm
Minimum Efficacy	97.11 lm/W	99.65 lm/W	102.18 lm/W
Power Factor	90.76%	90.76%	90.41%
THD	17.36%	17.36%	17.53%
CRI	81.1	81.1	81.6



Dauer LED panels are lay-in replacements for fluorescent fixtures. No mercury. Instant on-and-off. Highly efficient with a uniform, pleasant light. Aircraft-cable eye mounts. 0 to 10-volt dimming. Flicker-free. UL-approved. Easy installation. Designed for a 50,000-hour lifetime. Surface-mount kit available. Emergency power (>90 minutes) option is available.

DIMENSIONS:

