SPECIFICATION SHEET



Model:

ARIA 6" and 10" LED MR16 Uplight Fixture

ORDERING CODE:

489917-UP6 (6") 489917-UP10 (10")

SPECIFICATIONS

HOUSING:

Solid brass. Threaded with O-ring. Watertight and bug-tight.

FINISH:

Weathered brass. Architectural colors and custom powder coated colors available.

LENS:

Clear flat tempered glass.

SOCKET/LAMP HOLDER:

One fixed ceramic bi-pin socket with stainless steel retaining springs.

LAMP TYPE:

12V MR16. LED recommended. 30W halogen or 7W LED maximum.

MOUNTING:

Stake mount included.

WIRING:

Pre-wired with 5' pigtail of 18/2 cable.

WARRANTY:

Lifetime.

ARCHITECTURAL COLORS:

FINE TEXTURE SILVER	
FINE TEXTURE WHITE	
FINE TEXTURE BLACK	


Aria 6" Uplight (489917-UP6-S) Aria 10" Uplight (489917-UP10-S) Aria 6" Uplight (489917-UP6-WH) Aria 10" Uplight (489917-UP10-WH) Aria 6" Uplight (489917-UP6-BLK) Aria 10" Uplight (489917-UP10-BLK)


0



Standard colors: Bronze Aria 6" uplight (489917-UP6) / Bronze Aria 10" uplight (489917-UP10). Architectural colors and powder coated colors are also available.

DIMENSIONS:











SPECIFICATION SHEET Page 2 ARIA 6" and 10" LED MR16 Uplight Fixture

LED LAMP SPECIFICATIONS

LAMP TYPE:

12V Dauer MR16 lamp with 5-year warranty, dimmable, and suitable for enclosed luminaires.

OPTICS:

Integral optics providing available beam spreads from 15° to 120°.

COLOR TEMPERATURES:

Color temperature options provide the following qualities: 2700K or 3000K. Decorative color light options include amber, blue, green, red and purple.

To order a lamped fixture with mounting options, select the appropriate choice from each



EXAMPLE: 489917-UP6-4W-25-2700K-MS

column as in the following example:

FIXTURE ORDERING INFORMATION

FIXTURE		LAMP		MOUNTING	RISERS
489917-UP6 489917-UP6-S 489917-UP6-WH 489917-UP6-BLK 489917-UP10 489917-UP10-S 489917-UP10-WH 489917-UP10-BLK	WATTAGE	BEAM SPREAD	COLOR TEMP.	MS Composite stake (incl.) - 490034	R2 2-Inch Brass
	2W	25° / 40°/ 60° / 100°	2700K / 3000K	 M3 Trident Heavy-Duty 3-Prong Stake - 490036 PM Round pier mount - 490057 MR Round tapered 3-hole surface mount - 490048 	Riser - 490038 R3 3-Inch Brass Riser - 490039 R6 6-Inch Brass Riser - 490031
	3W	25° / 40°/ 60°	2700K / 3000K		
	4W	25° / 40°/ 60° / 100°	2700K / 3000K		
	5W -	15° / 25° / 40° / 60° / 100°	2700K / 3000K	MP PVC/Brass post stake - 490037	R12 12-Inch Brass
		25°	Amber / Blue / Green / Red	RMP Round Brass Electrical Mounting Plate - 490043	Riser - 490032
	5W	38°	Purple	REP Retangular Brass Electrical Mount-	R24 24-Inch Brass
	6W	25° / 40° / 60°	2700K / 3000K	ing Plate - 490044 GM Brass gutter mount 490047	Riser - 490033
	7W	15° / 30° / 45° / 60° / 120°	2700K / 3000K		

HQ: 10100 NW 116th way, Suite 14 | Medley, FL 33178 • Plant: 1430 Gould Blvd., Suite 3, La Vergne, TN 37086 800.883.2590 DauerManufacturing.com

