

Type:

Model:

LED Canopy Light

SPECIFICATIONS

VOLTAGE: 120 V to 270 V (347 V available)

DIMMING: Option for 0-10V step dimming

COLOR TEMPERATURE: 5000K or 4000K. 70 CRI.

LENS: Clear UV-stabilized polycarbonate sealed lens (frosted available via special order)

CONDUIT ENTRY POINTS: Three 1/2" and one 3/4" threaded

FINISH: Black (white and dark bronze available via special order)

AGENCY LISTINGS: DLC and UL approved (C29208419)

WARRANTY: Five years



Model	490600	490601	490606	490607
Description	LED-CGL-40CC-5000K	LED-CGL-40CC-5000K-DIM	LED-CGL-60CC-5000K	LED-CGL-60CC-5000K-DIM
Wattage	40 W	40 W	60 W	60 W
Dimming	No	0-10V Step	No	0-10V Step
Lens	Clear	Clear	Clear	Clear
Lumens	5,450	5,450	8,000	8,000
Efficacy	136 lm/W	136 lm/W	133 lm/W	133 lm/W

Ultra-thin embedded-LED canopy provides highly efficient and durable lighting for parking structures, storage areas, security lighting, schools, correctional facilities, and walkways. Die-cast aluminum housing. Replaces 100-watt to 175-watt metal-halide fixtures. Step-dimming option. Clear sealed polycarbonate lens. Suitable for damp locations. Surface or pendant mounting.



DIMENSIONS:

