

Type:

Model:



RoHS compliant



- 120-277V Input Voltage, 50/60Hz
- Driver UL Class 2, Power Factor >.90
- Ambient Operating Temperature -40°C (-40°F) to +40°C (105°F)
- Cast Aluminum Fitter
- Thermal Protection

- Estimated 50,000 hrs L₇₀
- 5-Year Warranty
- Posts Sold Separately
- Integral Surge Supression
- Optional Ground Surge Supression



CENTRAL PARK

GUIDE: DFP231-DL4000C-BW-B1

ITEM #	LIGHT SOURCE		BODY	LENS	OPTIONS
DFP231	120-277V LED	CCT	B -Black W -White Z -Bronze	ACRYLIC W -White C -Clear Prism	ACRYLIC BLACK-OUT PANELS B1 -One Panel B2 -Two Panels B3 -Three Panels
	DL4000 -40W 4000lm DL6000 -60W 6000lm	C -4K (Standard) W -3K (Special Order) B -5K (Special Order)			

499400 DFP231-DL4000C-BW **CENTRAL PARK** 40W Black with Acrylic White Lens
 499401 DFP231-DL4000C-BC **CENTRAL PARK** 40W Black with Acrylic Clear Prism Lens
 499402 DFP231-DL4000C-WW **CENTRAL PARK** 40W White with Acrylic White Lens
 499403 DFP231-DL4000C-WC **CENTRAL PARK** 40W White with Acrylic Clear Prism Lens
 499404 DFP231-DL4000C-ZW **CENTRAL PARK** 40W Bronze with Acrylic White Lens
 499405 DFP231-DL4000C-ZC **CENTRAL PARK** 40W Bronze with Acrylic Clear Prism Lens

499406 DFP231-DL6000C-BW **CENTRAL PARK** 60W Black with Acrylic White Lens
 499407 DFP231-DL6000C-BC **CENTRAL PARK** 60W Black with Acrylic Clear Prism Lens
 499408 DFP231-DL6000C-WW **CENTRAL PARK** 60W White with Acrylic White Lens
 499409 DFP231-DL6000C-WC **CENTRAL PARK** 60W White with Acrylic Clear Prism Lens
 499410 DFP231-DL6000C-ZW **CENTRAL PARK** 60W Bronze with Acrylic White Lens
 499411 DFP231-DL6000C-ZC **CENTRAL PARK** 60W Bronze with Acrylic Clear Prism Lens