

Type:

Model:

**LED High Bay**  
**SPECIFICATIONS**

**VOLTAGE:** 120 to 277V 50/60Hz or 347 to 480V 50/60Hz


**CRI:** 72

**HOUSING:** Die-cast aluminum with dark bronze powdercoat (white available with special order).

**OPERATING TEMPERATURE:** -40°F to 131°F.

**AGENCY LISTINGS:** UL approved.

**WARRANTY:** Five years.



Model	490650	490651	490652	490653
Description	LED-HB-140W-4000K-120°	LED-HB-140W-5000K-120°	LED-HB-200W-4000K-120°	LED-HB-200W-5000K-120°
Wattage	140W	140W	200W	200W
Voltage	120-277V	120-277V	120-277V	120-277V
Lumens	19,000 lm	19,000 lm	26,000 lm	26,000 lm
Efficacy	136 lm/W	136 lm/W	130 lm/W	130 lm/W
Equivalent	250W MH	250W MH	400W MH	400W MH
Model	490650-480V	490651-480V	490652-480V	490653-480V
Description	LED-HB-150W-4000K-120°	LED-HB-150W-5000K-120°	LED-HB-210W-4000K-120°	LED-HB-210W-5000K-120°
Wattage	150W	150W	210W	210W
Voltage	347-480V	347-480V	347-480V	347-480V
Lumens	19,000 lm	19,000 lm	26,000 lm	26,000 lm
Efficacy	127 lm/W	127 lm/W	124 lm/W	124 lm/W
Equivalent	400W MH	400W MH	400W MH	400W MH

Energy-saving high bay lights are ideal for commercial ceilings of 15 to 50 feet. Dauer high bays cast a productivity-enhancing light and reduce cooling costs. Die-cast aluminum housing with dark bronze finish. 10kV surge protection. Options for 0-10V dimming, one-off or diimmable motion sensor and/or photocell. Optional refractor or aluminum reflector.

**DIMENSIONS:**

