

Type:

Model:

LED Medium Area Lights

SPECIFICATIONS

VOLTAGE: 120 to 277 V 50/60 Hz or 347/480 V 50/60 Hz

COLOR TEMPERATURE: 5000 K (3000 K and 4000 K available)

POWER FACTOR: 90%

THD: <20%

HOUSING: Sealed one-piece cast aluminum with dark bronze powder coat. Custom powder coated colors available.

MOUNTING: Pole-mounting arm (square or round). Optional slipfitter, trunnion or wall mount. Stainless steel hardware.

OPTIONS: NEMA twist-lock photo control receptacle, PIR sensor (on/off or dimming).

AGENCY LISTINGS: DLC and UL approved. IP66.

WARRANTY: Five years.



Ideal for use in various architectural environments such as auto dealerships, parking lots, walkways, roadways, campuses, façade lighting, grocery stores and other public areas. Low-profile design with one-piece housing. Precision optics. 10kV/10kA surge protection. 0-10V dimmable.

Model	490644	490644-480V	490645	490645-480V
Description	LED-AL-150-5000K 120-277V	LED-AL-150-5000K 347-480V	LED-AL-200-5000K 120-277V	LED-AL-200-5000K 347-480V
Wattage	150 W	150 W	200 W	200 W
Voltage	120-277 V	347/480 V	120-277 V	347/480 V
Lumens	20,000 lm	20,000 lm	24,500 lm	24,500 lm
Efficacy	133 lm/W	133 lm/W	122 lm/W	122 lm/W
CRI	70	70	70	70
Equivalent	400 W MH	400 W MH	400 W MH	400 W MH
Distribution	Type 3, 4 or 5	Type 3, 4 or 5	Type 3, 4 or 5	Type 3, 4 or 5
Weight	16.5 lb Pole Mount 15.7 lb Slipfitter Mount	16.5 lb Pole Mount 15.7 lb Slipfitter Mount	16.5 lb Pole Mount 15.7 lb Slipfitter Mount	16.5 lb Pole Mount 15.7 lb Slipfitter Mount

