

Type:

Model:



RoHS compliant



- 120-277V Input Voltage, 50/60Hz
- Driver UL Class 2, Power Factor >.90
- Ambient Operating Temperature -40°C (-40°F) to +40°C (105°F)
- Cast Aluminum Fitter
- Thermal Protection

- Estimated 50,000 hrs L₇₀
- 5-Year Warranty
- Posts Sold Separately
- Integral Surge Supression
- Optional Ground Surge Supression



GUIDE: DFF240-DL4000C-BF

ITEM #	LIGHT SOURCE	CCT	BODY	LENS
DFF240	120-277V LED DL4000-40W 4000lm DL6000-60W 6000lm	C-4K (Standard) W-3K (Special Order) B-5K (Special Order)	B-Black W-White Z-Bronze	ACRYLIC W-White Drop Lens F-Frosted Flat Lens

- 499460 DFF240-DL4000C-BF ODYSSEY 40W Black with Frosted Flat Lens
- 499461 DFF240-DL4000C-BW ODYSSEY 40W Black with White Drop Lens
- 499462 DFF240-DL4000C-WF ODYSSEY 40W White with Frosted Flat Lens
- 499463 DFF240-DL4000C-WW ODYSSEY 40W White with White Drop Lens
- 499464 DFF240-DL4000C-ZF ODYSSEY 40W Bronze with Frosted Flat Lens
- 499465 DFF240-DL4000C-ZW ODYSSEY 40W Bronze with White Drop Lens

- 499466 DFF240-DL6000C-BF ODYSSEY 60W Black with Frosted Flat Lens
- 499467 DFF240-DL6000C-BW ODYSSEY 60W Black with White Drop Lens
- 499468 DFF240-DL6000C-WF ODYSSEY 60W White with Frosted Flat Lens
- 499469 DFF240-DL6000C-WW ODYSSEY 60W White with White Drop Lens
- 499470 DFF240-DL6000C-ZF ODYSSEY 60W Bronze with Frosted Flat Lens
- 499471 DFF240-DL6000C-ZW ODYSSEY 60W Bronze with White Drop Lens