

Type:

Model:

LED Small Area Lights
SPECIFICATIONS

VOLTAGE: 120 to 277 V 50/60 Hz (347 to 480 V available)

COLOR TEMPERATURE: 5000 K (3000 K and 4000 K available)

POWER FACTOR: 90%

THD: <20%

HOUSING: Sealed one-piece cast aluminum with dark bronze powder coat. Custom powder coated colors available.

MOUNTING: Pole-mounting arm (square or round). Optional slipfitter, trunnion or wall mount. Stainless steel hardware.

OPTIONS: NEMA twist-lock photo control receptacle, 0-10V dimming, PIR sensor (on/off or dimming).

AGENCY LISTINGS: DLC and UL approved. IP66.

WARRANTY: Five years.



Ideal for use in various architectural environments such as auto dealerships, parking lots, walkways, roadways, campuses, façade lighting, grocery stores and other public areas. Low-profile design with one-piece housing. Precision optics. 10kV/10kA surge protection.

Model	490642	490642-480V	490643	490643-480V
Description	LED-AL-70-5000K 120-277V	LED-AL-75-5000K 347/480V	LED-AL-105-5000K 120-277V	LED-AL-110-5000K 347/480V
Wattage	70 W	75 W	105 W	110 W
Voltage	120-277 V	347/480 V	120-277 V	347/480 V
Lumens	9,000 lm	9,000 lm	13,400 lm	13,400 lm
Efficacy	128 lm/W	120 lm/W	127 lm/W	122 lm/W
CRI	70	70	70	70
Equivalent	250 W MH	250 W MH	320 W MH	320 W MH
Distribution	Type 3 or 5	Type 3 or 5	Type 3 or 5	Type 3 or 5

DIMENSIONS:

