

# SPECIFICATION SHEET

Type:

Model:

# WENTWORTH Adjustable Gimbal Well Light Fixture

### **ORDERING CODE:**

490071

### **SPECIFICATIONS**

#### **HOUSING:**

Cast brass faceplate. (Opens with 3 mm hex key.) Composite body. Aluminum gimbal.

#### FINISH:

Weathered brass. Custom powder coated colors available.

#### **SOCKET/LAMP HOLDER:**

One ceramic GU5.3 bi-pin socket with stainless steel retaining springs, on an adjustible gimbal, accepts MR16 lamps with G4 or GY6.35 bases.

#### LENS:

Flat tempered glass.

#### **LAMP TYPE:**

12V MR16. LED recommended. Halogen 30W maximum or 7W LED maximum.

#### **MOUNTING:**

Installs in-grade. Can replace a standard 6-inch-square paver.

#### WIRING

Pre-wired with 5' pigtail of 18/2 cable.

#### **WARRANTY**:

Lifetime.



The Wentworth well light has an easily adjustable gimbal mechanism that allows precise aiming of the lamp for angled uplighting. Cast brass faceplate with a gasketed heavy-duty composite body. Can replace a standard 6-inch-square driveway paver.

## **DIMENSIONS:**







### **LED LAMP SPECIFICATIONS**

#### **LAMP TYPE:**

12V Dauer MR16 lamp with 5-year warranty, dimmable, and suitable for enclosed luminaires.

#### **OPTICS:**

Integral optics providing available beam spreads from 15° to 100°.

#### **COLOR TEMPERATURES:**

Color temperature options provide the following qualities: 2700K or 3000K. Decorative color light options include amber, blue, green, red and purple.

### FIXTURE ORDERING INFORMATION

To order a lamped fixture with mounting options, select the appropriate choice from each column as in the following example:

EXAMPLE: 490071-MR16-4W-25-2700K

FIXTURE		LAMP	
490071	WATTAGE	BEAM SPREAD	COLOR TEMP.
	2W	25° / 40° / 60° / 100°	2700K / 3000K
	3W	25° / 40° / 60°	2700K / 3000K
	4W	25° / 40° / 60° / 100°	2700K / 3000K
	5W	15° / 25° / 40° / 60° / 100°	2700K / 3000K
		25°	Amber / Blue / Green / Red
	5W	38°	Purple
	6W	25° / 40° / 60°	2700K / 3000K
	7W	15° / 30° / 45° / 60° / 120°	2700K / 3000K



