




KEY FEATURES | DFP171 ASTON

- Fade & Rust Resistant Composite Construction
- UL Listed for Wet Locations
- Mounting Hardware Included

EXTENDS:
4"
H/CTR:
5 1/2"
BACKPLATE:
7 1/4" X 9 1/2"



DFP171



EXAMPLE # DFP171-I40-ZF-LWE

STYLE #	LIGHT SOURCE	BODY	DIFFUSER	OPTIONS
DFP171	DEDICATED 120V LED EOS LED 120V AC, 50/60 Hz, HPF, 50,000 HRS L70, AMBIENT OP TEMP -40°C TO +40°C, 5 YEAR WARRANTY, DIMMABLE LL900 - 10W, 80 CRI W-930lm 3000K C-970lm 4000K	B-Black W-White Z-Bronze	ACRYLIC F-Frost	P-Photocell 120V only.
	INCANDESCENT 120V INCANDESCENT, MEDIUM BASE, 120V I40-1 X 40W Max			P-Photocell 120V only. LED LAMP, 3 YEAR WARRANTY, DIMMABLE LWE-A19/E26, 90CRI, 3000K LCE-A19/E26, 80CRI, 4000K

Data per LM79/LM80/TM21 available upon request. Specification subject to change without notice.